

50th year

DATASHEET



E SERIES

MODULAR SYSTEM

POWER DISTRIBUTION

INDOOR

CRS

DATASHEET

E SERIES

MODULAR SYSTEM

POWER DISTRIBUTION

INDOOR

CRS

yespan®



DIMENSIONS

WIDTH mm	HEIGHT mm	DEPTH mm
400	1800	400
500	2000	500
600	2200	600
700		800
800		1000
1000		1200
1200		

MATERIAL DETAILS	THICKNESS	MATERIAL	COATING
Enclosure Frame	2,00 mm	275 gr/m ² Galvanized CRS	Unpainted
Door	2,00 mm	CRS	7035
Side/Back Wall	1,00 mm	CRS	7035
Bottom Plate	1,50 mm	275 gr/m ² Galvanized CRS	Unpainted
Top Plate	2,00 mm	275 gr/m ² Galvanized CRS	7035
Plinth Cover	2,00 mm	CRS	9005
Plinth Corner	2,50 mm	275 gr/m ² Galvanized CRS	Unpainted
Cover Plates	1,00 mm	CRS	7035

DATASHEET

E SERIES

yespan®

MODULAR SYSTEM

POWER DISTRIBUTION

INDOOR

CRS

PROTECTION CLASS

: IP40 / IP55

IK CODE

: IK10

SURFACE TREATMENT

: Nanoceramic coating

COATING

: Ral 7035 wrinkle UV resistive polyester powder coating

LOCK

: Polyamide handle with key, 4 points latch

HINGES

: Hidden hinges, zinc coated.
130° opening angle

INSETS

: Door earthing cable (1 piece for each door)

GTIP CODE

: 8538.10.00.00.00

CERTIFICATES

: IEC 62208-TSE	IEC TR 61439 - 4000A
IP55 Test	IEC TR 61439 - 4000A - FORM 4B
IK10 Test	IEC TR 61641 - Internal Arc Test
EAC Certificate	IEC 60068-3-3 Seismic Test
RED Certificate	GR63 Core Seismic Test
	ASTM 4169-16 Transportation Test

DECLARATIONS

: CE Declaration of Conformity

YESPAN ELEKTRİK SANAYİ VE TİCARET LTD. ŞTİ.

Head Office : Umurlu mahallesi Aydın OSB 2.Cadde No:41 09630 Efeler / AYDIN - TÜRKİYE
Phone : +90.256. 211 56 56 pbx • info@yespan.com

Branch : Perpa Ticaret Merkezi A Blok Kat: 11 No: 1667 Şişli / İSTANBUL - TÜRKİYE

