

50th year

DATASHEET



B SERIES

COMPACT ENCLOSURES

POWER DISTRIBUTION

OUTDOOR

CRS

DATASHEET

B SERIES

yespan®

COMPACT ENCLOSURES

POWER DISTRIBUTION

OUTDOOR

CRS



DIMENSIONS

WIDTH mm	HEIGHT mm	DEPTH mm
500	650	300
600	900	400
	1050	
	1200	

MATERIAL DETAILS	THICKNESS	MATERIAL	COATING
Enclosure Frame	1,00 mm - 1,50 mm	CRS	7035
Door	1,00 mm - 1,50 mm	CRS	7035
Bottom Plate	1,50 mm	CRS	7035
Top Plate	1,50 mm	CRS	7035
Cover Plates	1,00 mm	CRS	7035
Canopy	1,00 mm - 1,50 mm	CRS	7035

OPTIONAL DETAILS	THICKNESS	MATERIAL	COATING
Plinth	2,00 mm	CRS	9005

DATASHEET

B SERIES

yespan®

COMPACT ENCLOSURES

POWER DISTRIBUTION

OUTDOOR

CRS

PROTECTION CLASS

: IP66

IK CODE

: IK10

SURFACE TREATMENT

: Nanoceramic coating

COATING

: Ral 7035 wrinkle UV resistive polyester powder coating

LOCK

: Quarter Turn Lock with DB key

HINGES

: Hidden hinges, stainless steel.
130° opening angle

INSETS

: Door earthing cable (1 piece for each door)

GTIP CODE

: 8538.10.00.00.00

CERTIFICATES

: IEC 62208-TSE
IP66 Test
IK10 Test
EAC Certificate
RED Certificate

DECLARATIONS

: CE Declaration of Conformity

YESPAN ELEKTRİK SANAYİ VE TİCARET LTD. ŞTİ.

Head Office : Umurlu mahallesi Aydın OSB 2.Cadde No:41 09630 Efeler / AYDIN - TÜRKİYE
Phone : +90.256. 211 56 56 pbx • info@yespan.com

Branch : Perpa Ticaret Merkezi A Blok Kat: 11 No: 1667 Şişli / İSTANBUL - TÜRKİYE

